

2. Specifications

Type		4 Way Ceiling Mounted Cassette	
Model		Unit	WF4A130CG0A
Power Supply		V, Φ , Hz	220-230-240, 1, 50/60
Running Current by Voltage		A	1.7-1.88-1.88
Capacity	Cooling	Condition A	13.0(11,178)
		Condition B	8.7(7,481)
		Condition C	10.5(9,028)
		Condition D	5.3(4,557)
	Heating	Condition A	13.3(11,436)
		Condition B	15.7(13,500)
Water Flow Rate	Cooling	Condition A	37.8
		Condition B	28.6
		Condition C	37.8
		Condition D	24.1
	Heating	Condition A	39.1
		Condition B	37.8
Head Loss	Cooling	Condition A	68.2
		Condition B	38.9
		Condition C	68.2
		Condition D	26.4
	Heating	Condition A	71.7
		Condition B	68.3
Power Input	Nominal	W	246
Running Current	Nominal	A	1.88
Fan	Type	-	Turbo Fan
	Air Flow Rate(H/M/L)	m ³ /min	41.0/36.0/30.0
Fan Motor	Type	-	BLDC
	Drive	-	CCW
	Output	W x No.	136x1
	FLA(Full Load Ampere)	A	1.88
Dimensions	Net (W x H x D)	mm	840 x 288 x 840
Weight	Net	kg	25.1
	Shipping	kg	29.7
Air Filter	Type	-	-
Temperature Control	-	-	Microprocessor, Thermostat for cooling and heating
Sound Absorbing / Thermal Insulation Material	-	-	Foamed polystyrene
Protection Device	-	-	Fuse
Water Connecting Pipes	Inlet	-	BSPF G 3/4"(male)
	Outlet	-	BSPF G 3/4"(male)
Sound Pressure Level	Cooling(H/M/L)	dB(A)	57/53/50
	Heating(H/M/L)	dB(A)	57/53/50
Sound Power Level	Cooling(H/M/L)	dB(A)	65/61/57
	Heating(H/M/L)	dB(A)	65/61/57
Connecting Cable	Communication Cable(VCTF-SB)	mm ² xcores	1.0 ~ 1.5
Decoration Panel #1 (Accessory)	Name	-	PT-MCHW0
	Dimensions(W x H x D)	mm	950 x 35 x 950
	Color	-	Morning fog
	RAL Code	-	120-4
Decoration Panel #2 (Accessory)	Name	-	-
	Dimensions(W x H x D)	mm	-
	Color	-	-
	RAL Code	-	-

Note

- Due to our policy of innovation some specifications may be changed without notification.
- Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
- Sound Level Values are measured at Noise Measuring chamber accordance with standard. Therefore, these values depend on the ambient conditions and values are normally higher in actual operation.
- Performances are based on the following conditions :
 - Cooling
 - Condition A : Inlet/Outlet Water Temp. 7°C / 12°C, Indoor Air Temp. 27°CDB / 19°CWB
 - Condition B : Inlet/Outlet Water Temp. 10°C / 15°C, Indoor Air Temp. 27°CDB / 19°CWB
 - Condition C : Inlet/Outlet Water Temp. 7°C / 12°C, Indoor Air Temp. 25°CDB / 17.9°CWB
 - Condition D : Inlet/Outlet Water Temp. 14°C / 18°C, Indoor Air Temp. 26°CDB / 18°CWB
 - Heating
 - Condition A : Inlet/Outlet Water Temp. 45°C / 40°C, Indoor Air Temp. 20°CDB / 15°CWB
 - Condition B : Inlet Water Temp. 50°C, Indoor Air Temp. 20°CDB / 15°CWB
- Capacity, power consumption, etc. may vary depending on the product installation conditions (temperature, conditions of use).
- Main power line should be shorter than 50m. When installing a power line longer than 50m, contact LG Electronics.
- Water connecting pipes are in accordance with the DIN-EN-ISO 228-1 standard.